

DECLARATION OF PERFORMANCE DT002

Visually strength graded structural timber (D24/D30/ D40 timber)

Construction Product

Visually strength graded structural timber (according to BS 5756) which fulfils the requirements of EN 14081-1:2005+A1:2011

Intended use of the construction product

For load-bearing purposes in construction works designed according to Eurocode 5 (EN 1995) and for other uses where adequate strength and stiffness of the structure is essential.

Producer / Manufacturer

Duffield Timber
Green Lane
Melmerby
Ripon
North Yorkshire
HG4 5JB

Tel 01765 640564 Fax 01765 640750

Email mike.hall@duffieldtimber.com

web www.duffieldtimber.com

System of assessment and verification of constancy of performance of the construction product

System 2+

Certification

The notified body Exova BM TRADA Certification Limited has performed the initial inspection of the manufacturing plant and of the factory production control and continues to perform continuous surveillance, assessment and evaluation of the factory production control.

Exova BM TRADA Certification Limited has issued the certificate of conformity of the factory production control N° 2812-CPR-0382

GREEN LANE, MELMERBY, RIPON
NORTH YORKSHIRE, HG4 5JB

TEL: (01765) 640564/640499

FAX: (01765) 640750

SALES FAX: (01765) 640600

Email: sales@duffieldtimber.com

Chairman: Robert E. Duffield
Managing Director: Howard R. Duffield
Directors: A. Duffield, A.D. Flinton
D. Lees, N.T. Collinson

Registered in England
Company Registration No. 1305703
VAT Registration No. 301 1004 54

Declared Performance

The performance of the visually strength graded structural timber (according to BS 5756) is in conformity with the harmonised European Standard EN 14081- 1:2005+A1:2011 Timber Structures – Strength graded structural timber with rectangular cross section – Part 1: General Requirements

Essential Characteristics	Declared Performance	
Species/species group	Oak QCXE	EN 14081-1:2005
Growth area	France	
Range of thickness	50 – 400mm	
Range of width	100 – 400mm	
Surface finish	Sawn / Planed	
Graded	Wet graded	
Grade/grading standard	D24/D30/D40	BS 5756:2007
Strength, stiffness and density	French Oak	EN 338:2009
Durability (may contain sapwood)	2-3	EN 350-2:1994
Reaction to fire	D-s2, d0	EN 14081-1, Table C.1
Release of dangerous substances	NPD	

Authorisation

This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

For and on behalf of Duffield Timber

Mike Hall,
Registered Grader 5116
Ripon, North Yorkshire – 6 November 2017

GREEN LANE, MELMERBY, RIPON
NORTH YORKSHIRE, HG4 5JB

TEL: (01765) 640564/640499
FAX: (01765) 640750
SALES FAX: (01765) 640600
Email: sales@duffieldtimber.com

Chairman: Robert E. Duffield
Managing Director: Howard R. Duffield
Directors: A. Duffield, A.D. Flinton
D. Lees, N.T. Collinson

Registered in England
Company Registration No. 1305703
VAT Registration No. 301 1004 54